

# RB2011UiAS

RouterBOARD 2011UiAS, in comparison with RB2011L series, not only has five Gigabit LAN ports and five Fast Ethernet LAN ports, but also has RJ45 serial port, microUSB port and more RAM (128MB instead of 64MB). Also, it has RouterOS L5 license (instead of L4) and nice touchscreen LCD for configuration. SFP cage is also present (SFP module not included!)

RouterBOARD 2011UiAS series includes two models- RB2011UiAS-IN (desktop enclosure) and RB2011UiAS-RM (1U rackmount enclosure). Both models includes power supply and support power output on port 10 (up to 500mA).



RB2011UiAS-IN



RB2011UiAS-RM

CPU	Atheros AR9344 600MHz
Memory	128MB DDR SDRAM onboard memory
Ethernet	Five 10/100 Mbit Fast Ethernet ports with Auto-MDI/X Five 10/100/1000 Mbit Gigabit Ethernet ports with Auto-MDI/X
Expansion	SFP port
Extras	Reset button, Reset jumper
LEDs	Power, User, Ethernet activity
Power options	Jack 8-28V DC; PoE: 8-28V DC on Ether1 (Non 802.3af).
Dimensions	214 mm x 86 mm, Weight: 146g
Power consumption	15W max
Power output	500mA on Port 10
Operating System	MikroTik RouterOS, L5 license
Package includes	RB2011, power supply, (depends on model: enclosure)

Feature / Model	2011UiAS-IN	2011UiAS-RM
Enclosure	Desktop	Rackmount
SFP port	Yes	Yes
LCD display	Yes	Yes
Serial port	Yes	Yes
USB	Yes	Yes
Wireless	-	-
Power output	port 10	port 10